Project title: Innovative lightweight cold-formed steel-concrete composite floor system Acronym: LWT-FLOOR Project ID: UIP-2020-02-2964 3rd LWT-FLOOR Project Workshop

Finite Element Analyses of Demountable Shear Connection in Cold-Formed Steel-Concrete Composite Beam Based on Experimental Data

Vlaho Žuvelek | Ivan Ćurković | Ivan Lukačević | Andrea Rajić





University of Zagreb/Faculty of Civil Engineering http://www.grad.unizg.hr/lwtfloor

Agenda



- Introduction
- Experimental programme
- Finite element (FE) model
 - Geometry, boundary conditions and loading
 - Mesh, interactions and analysis method
 - Constitutive models
 - Validation of numerical models
- Parametric study
- Results and discussion
- Conclusions



University of Zagreb Faculty of Civil Engineering LWT-FLOOR Project <u>http://www.grad.unizg.hr/lwtfloor</u>

1. Introduction







University of Zagreb Faculty of Civil Engineering LWT-FLOOR Project http://www.grad.unizg.hr/lwtfloor

1. Introduction







University of Zagreb Faculty of Civil Engineering LWT-FLOOR Project http://www.grad.unizg.hr/lwtfloor







University of Zagreb Faculty of Civil Engineering LWT-FLOOR Project http://www.grad.unizg.hr/lwtfloor

Thickness of tested steel sheets: **0.8** mm **1**.0 mm **1.25 mm 1**.5 mm **2.0 mm 2**.5 mm **3.0** mm





University of Zagreb Faculty of Civil Engineering LWT-FLOOR Project http://www.grad.unizg.hr/lwtfloor



• Thickness of tested steel sheets:

0.8 mm
1.0 mm
1.25 mm
1.5 mm
2.0 mm
2.5 mm
3.0 mm





University of Zagreb Faculty of Civil Engineering LWT-FLOOR Project http://www.grad.unizg.hr/lwtfloor

Thickness of tested steel sheets: **0.8** mm **1**.0 mm **1.25 mm 1.5 mm 2.0 mm Q**2.5 mm **3.0** mm

BH_ 3.0.04	ISNARD TO T
BN- 30- 02	
BH_30-03	+ +
BH_ 3.0_ 04	
BH_ 3.0-05	A DATE OF A
BH_30_06	
BM_ 3.0_ 07	
BH_30-08	
BM-30-09	
BH_30-10	



University of Zagreb Faculty of Civil Engineering LWT-FLOOR Project http://www.grad.unizg.hr/lwtfloor









University of Zagreb Faculty of Civil Engineering LWT-FLOOR Project http://www.grad.unizg.hr/lwtfloor

- Concrete:
 - Normal weight concrete (NC)
 - 15 concrete cylinders
- Crushing and modulus elasticity





	Compressive	Modulus of
	strength	elasticity
	[MPa]	[MPa]
Mean value	28.09	29526
St. dev. [%]	2.429	0.281
Coefficient of variation [%]	8.64	0.95





University of Zagreb Faculty of Civil Engineering LWT-FLOOR Project http://www.grad.unizg.hr/lwtfloor



Reinforcement mesh and bars





University of Zagreb Faculty of Civil Engineering LWT-FLOOR Project http://www.grad.unizg.hr/lwtfloor



- Bolts:
 - M12
 - M16









University of Zagreb Faculty of Civil Engineering LWT-FLOOR Project http://www.grad.unizg.hr/lwtfloor

INT-FLOOR BESLIGE PROPERT

Combination of sheet thicknesses for spot welds:

- 0.8 mm 0.8 mm
- 0.8 mm 1.0 mm
- 0.8 mm 1.25 mm
- 0.8 mm 1.5 mm
- 0.8 mm 2.0 mm
- 0.8 mm 2.5 mm
- 0.8 mm 3.0 mm
- 1.0 mm 1.0 mm
- 1.0 mm 1.25 mm
- 1.0 mm 1.5 mm
- 1.0 mm 2.0 mm
- 1.0 mm 2.5 mm
- 1.0 mm 3.0 mm
- 1.25 mm 1.25 mm
- 1.25 mm 1.5 mm
- 1.25 mm 2.0 mm

- 1.25 mm 2.5 mm
- 1.25 mm 3.0 mm
- 1.5 mm 1.5 mm
- 1.5 mm 2.0 mm
- 1.5 mm 2.5 mm
- 1.5 mm 3.0 mm
- 2.0 mm 2.0 mm
- 2.0 mm 2.5 mm
- 2.0 mm 3.0 mm
- 2.5 mm 2.5 mm
- 2.5 mm 3.0 mm
- 3.0 mm 3.0 mm
- Total: 558 specimens



University of Zagreb Faculty of Civil Engineering LWT-FLOOR Project http://www.grad.unizg.hr/lwtfloor













University of Zagreb Faculty of Civil Engineering LWT-FLOOR Project http://www.grad.unizg.hr/lwtfloor

- Idea and design of push-out specimens:
 - CFS 120x47x3 mm
 - Concrete slab 720x600x120 mm
 - Profiled steel sheeting 720x600x1.0 mm
 - Corrugated web 780x120x1.25 mm
 - Bolts M12 & M16, steel grade 8.8







University of Zagreb Faculty of Civil Engineering LWT-FLOOR Project http://www.grad.unizg.hr/lwtfloor



• Fabrication process of bolted shear connection specimens





University of Zagreb Faculty of Civil Engineering LWT-FLOOR Project http://www.grad.unizg.hr/lwtfloor



Implementation of testing of push-out samples
 ✓ Loading program was considered based on Eurocode 4-Annex
 B





University of Zagreb Faculty of Civil Engineering LWT-FLOOR Project http://www.grad.unizg.hr/lwtfloor



• Implementation of testing of push-out samples





University of Zagreb Faculty of Civil Engineering LWT-FLOOR Project http://www.grad.unizg.hr/lwtfloor

IWT-FLOOR BUSLIKE PROBET

- Analysis and processing of results
 - The statistical evaluation of experimental results according to EN1990 - Annex D

Crasimor	Force [kN]	Slip [mm]		300	RCV		1	BCWB_04
Specimen	Ultimate	Initial	Failure	250		V		BCWB_05
	P _{ult}	δ _{int}	δ _u	200				
BCWB_04	267	0.59	6.82	$\left[\sum_{n=1}^{200} \right]$		11-	!	
BCWB_05	263	1.66	8.27	ອ ອຸ 150				
BCWB_06	259	1.09	5.67					δ_{int} δ_{u}
Mean	263		6.92			1	 I I	0.40 Put
Coefficient of variation [%]	1.52	-	18.82	50				$\uparrow \delta_{int} \qquad \delta_{int}$
Characteristic	250	1-12	2.53		0	2	4	6 8 10 12 14
					-	-	•	Slip [mm]



University of Zagreb Faculty of Civil Engineering LWT-FLOOR Project http://www.grad.unizg.hr/lwtfloor

- Bolted shear connection (embedded nuts)

 Increased stiffness
 Easier mounting
- Direct shear force transmission
- Two systems configuration:
 - o Built-up CFS girder
 - Back-to-back CFS girder



University of Zagreb Faculty of Civil Engineering LWT-FLOOR Project http://www.grad.unizg.hr/lwtfloor Project title: Innovative lightweight cold-formed steel-concrete composite floor system Acronym: LWT-FLOOR Project ID: UIP-2020-02-2964 3rd LWT-FLOOR Project Workshop



20



3rd LWT-FLOOR Project Workshop



Load

Uniform vertical

- Horizontal directions
- CFS top

Bottom concrete plane

All directions

- Symmetric boundary conditions



3. Finite element (FE) model

Plane orthogonal to the X-axis

displacement at the CFS top







Interaction

Normal behaviour

 \circ Hard contact

o Tangential behaviour

Penalty friction (0.1, 0.3 and 0.5 frictional coefficient)

Spot welds

Bushing type connectors

Elasticity, Plasticity, Damage and Failure characteristics



University of Zagreb Faculty of Civil Engineering LWT-FLOOR Project http://www.grad.unizg.hr/lwtfloor

- Constitutive models

 Steel
 - True stress-strain curve adopted based on experimental results
 - o Concrete
 - Concrete Damage Plasticity (CDP) model
 - Compression failure
 - Tension failure







University of Zagreb Faculty of Civil Engineering LWT-FLOOR Project http://www.grad.unizg.hr/lwtfloor

- Validation of numerical models
 - Good agreement between experimental and numerical results
 - Benchmark model for parametric analyses





University of Zagreb Faculty of Civil Engineering LWT-FLOOR Project http://www.grad.unizg.hr/lwtfloor Project title: Innovative lightweight cold-formed steel-concrete composite floor system Acronym: LWT-FLOOR Project ID: UIP-2020-02-2964 3rd LWT-FLOOR Project Workshop Croatian Scien Foundation

LWT-FLOO



Validation of numerical models







University of Zagreb Faculty of Civil Engineering LWT-FLOOR Project http://www.grad.unizg.hr/lwtfloor

4. Parametric study



 Two configurations of CFS-concrete composite systems were analysed.

Model name	Bolt	Bolt position	Corrugated web
BB_P1	M12	Pairs	×
BB_S1	M12	Staggered	×
BB_P2	M16	Pairs	×
BB_S2	M16	Staggered	×
BCWB_P1	M12	Pairs	1
BCWB_S1	M12	Staggered	1
BCWB_P2	M16	Pairs	\checkmark
BCWB_S2	M16	Staggered	\checkmark

Note:

BB_xx - configuration without corrugated web

BCWB_xx - configuration with corrugated web



University of Zagreb Faculty of Civil Engineering LWT-FLOOR Project http://www.grad.unizg.hr/lwtfloor

5. Results and discussion



- Several failure modes can occur together
- BB_Px models with two bolts per rib- Lower resistance = concrete failure (overlaping area)
- Models with one bolt per rib
 - Development of the full bearing capacity of shear connection.





University of Zagreb Faculty of Civil Engineering LWT-FLOOR Project http://www.grad.unizg.hr/lwtfloor

6. Conclusions



- Using the FE model, it was confirmed that bolted shear connections in concrete CFS beams mostly exhibit multiple failure modes and that the interaction between these modes has an influence on the behaviour and resistance of the specimen.
- Placing two bolts per rib at a close transverse spacing (BB models), early concrete failure occurs due to the overlap of the failure areas. Therefore, the system configuration with a corrugated web (BCWB models) achieves a more favourable behaviour in terms of resistance and ductility when two bolts per rib are installed.
- Models with one bolt per rib placed in a staggered position allowed the development of the full bearing capacity of the shear connection, regardless of whether the system configuration including a corrugated web or not.



University of Zagreb Faculty of Civil Engineering LWT-FLOOR Project http://www.grad.unizg.hr/lwtfloor Project title: Innovative lightweight cold-formed steel-concrete composite floor system Acronym: LWT-FLOOR Project ID: UIP-2020-02-2964 3rd LWT-FLOOR Project Workshop

Thank you for attention!

Finite Element Analyses of Demountable Shear Connection in Cold-Formed Steel-Concrete Composite Beam Based on Experimental Data

Vlaho Žuvelek | Ivan Ćurković | Ivan Lukačević | Andrea Rajić





University of Zagreb/Faculty of Civil Engineering http://www.grad.unizg.hr/lwtfloor